



## PARAFFIN FULLY SYNTHETIC MOTOR OIL SAE 10W-40

The Right Choice in Lubricants

**PARAFFIN FULLY SYNTHETIC ENGINE OIL SAE10W-40** is a multi-grade high-performance gasoline engine oil, formulated to perform in all driving conditions, from mild to severe. PARAFFIN FULLY SYNTHETIC ENGINE OIL SAE10W-40 offers control of piston and ring deposits, removing sludge and keeping the valve train, crankcase, and oil filter clean. It creates good sealing between the piston and cylinder, protects the engine at different temperatures and maintains optimum viscosity for the best engine performance.

### FEATURES AND BENEFITS

- Protection against Engine Wear & Tear
- Battles Deposits & Sludge Formation
- Good Oxidation Stability
- Good Thermal Stability

### APPLICATION

It is recommended for naturally aspirated and multi-valve fuel injected high-performance gasoline engines, Appropriate for passenger cars, SUVs, vans and light commercial vehicles.

### TYPICAL TECHNICAL PROPERTIES

TEST PARAMETERS	TEST METHOD	TYPICAL VALUE
APPEARANCE	VISUAL	CLEAR
COLOR	ASTM D1500	L2
SPECIFIC GRAVITY @ 15°C	ASTM D1298	0.870
FLASH POINT, (C.O.C.)	ASTM D92	230°C
VISCOSITY @ 100 °C, cSt	ASTM D445	13.2
VISCOSITY @ 40 °C, cSt	ASTM D445	88.70
POUR POINT, °C	ASTM D97	-42
T.B.N., mg KOH/g	ASTM 2896	11.50
FOAM TEST, ml Seq. I	ASTM D892	10/0
Seq. II	ASTM D892	10/0
Seq. III	ASTM D892	0/0
VISCOSITY INDEX	ASTM D2270	150
Apparent viscosity(MRV),CCS	ASTM D5293	3600



### SPECIFICATION

API SP, SN, SM, SL/CF

📍 Al Ghail Industrial Park - Ras Al Khaimah - United Arab Emirates

☎ +971 7 266 7906 📞 +971 50 327 2769 📱 📧

✉ sales@paraffinlubricants.com 🌐 www.paraffinlubricants.com

📘 paraffinoilrefineryandmanufacturing 📷 paraffinoilmanufacturing

📦 Packaging Sizes: 1L 3L 4L 5L 20L 25L 208L