



PARAFFIN FULLY SYNTHETIC MOTOR OIL SAE 10W-60

The Right Choice in Lubricants

PARAFFIN FULLY SYNTHETIC ENGINE OIL SAE10W-60 is Fully synthetic high-performance 4-stroke engine oil, specially developed for demanding use in hyper sport motorcycles with powerful engines. These lubrications provide engines, gearboxes and clutches with optimum protection over the entire range of applications. JASO MAZ approval guarantees the fault-free functioning of wet multi-disc clutches.

FEATURES AND BENEFITS

- Serious power delivery
- Racing quality
- Optimum wear protection
- Extremely good thermal and shear stability
- Catalytic converter tested

APPLICATION

Available in three different viscosities, It is specially designed for sporting use. Ideal for high-performance motorcycles with wet multi-disc clutches. Also meets the highest manufacturer's specifications.

TYPICAL TECHNICAL PROPERTIES

TEST PARAMETERS	TEST METHOD	TYPICAL VALUE
APPEARANCE	VISUAL	CLEAR
COLOR	ASTM D1500	L2
SPECIFIC GRAVITY @ 15°C	ASTM D1298	0.870
FLASH POINT, (C.O.C.)	ASTM D92	230°C
VISCOSITY @ 100 °C, cSt	ASTM D445	22.5
VISCOSITY @ 40 °C, cSt	ASTM D445	184.2
POUR POINT, °C	ASTM D97	-38
T.B.N., mg KOH/g	ASTM 2896	11.50
FOAM TEST, ml Seq. I	ASTM D892	10/0
Seq. II	ASTM D892	10/0
Seq. III	ASTM D892	0/0
VISCOSITY INDEX	ASTM D2270	148
Apparent viscosity(MRV),CCS	ASTM D5293	3600



SPECIFICATION

API SP, SN, SM, SL/CF

📍 Al Ghail Industrial Park - Ras Al Khaimah - United Arab Emirates

☎ +971 7 266 7906 📞 +971 50 327 2769 📧 📱

✉ sales@paraffinlubricants.com 🌐 www.paraffinlubricants.com

📘 paraffinoilrefineryandmanufacturing 📷 paraffinoilmanufacturing

Packaging Sizes: 1L 3L 4L 5L 20L 25L 208L