



# PARAFFIN CVT FLUID

The Right Choice in Lubricants

**PARAFFIN ATF CVT FLUID** is a fully synthetic ultra-high performance CVT fluid formulated with selected base stocks and specially developed for use in the latest generation of Continuously Variable Transmission (CVT) – gearboxes which transfer traction via steel-made traction chain or push-belts. It is formulated on high refined synthetic base stock in combination with a unique additive package to reach the following properties.

## FEATURES AND BENEFITS

- High Viscosity Index ensures adequate lubrication in both high operating & low starting temperatures.
- Better foam control leads to smooth & lasting shift feel and reduces fluid loss.
- Enhanced Low temperature fluidity assist in good cold start performance.
- Excellent anti-wear, anti-rust and anti-corrosion technology.

## APPLICATION

CVT Fluid is recommended for service fill use in the passenger car, push-belt and chain-driven continuously variable transmission applications where CVT fluids are recommended only. (except for CVTs that require gear oils, and toroidal CVTs).

## TYPICAL TECHNICAL PROPERTIES

TEST PARAMETERS	TEST METHOD	TYPICAL VALUE
VISCOSITY @ 100 °C, cSt	ASTM D445	7.2
VISCOSITY @ 40 °C, cSt	ASTM D445	33.7
POUR POINT, °C	ASTM D97	-48°C
FOAM TEST, ml Seq. I	ASTM D892	10/0
Seq. II	ASTM D892	10/0
Seq. III	ASTM D892	0/0
FLASH POINT, (C.O.C.)	ASTM D92	220°C
Density @ 15°C kg/l	ASTM D-1298	0.845
VISCOSITY INDEX	ASTM D2270	185
Brookfield Viscosity @ -40°C cp	ASTM 2983	9020



📍 Al Ghail Industrial Park - Ras Al Khaimah - United Arab Emirates

☎ +971 7 266 7906 📞 +971 50 327 2769 📧 📱

✉ sales@paraffinlubricants.com 🌐 www.paraffinlubricants.com

📘 paraffinoilrefineryandmanufacturing 📷 paraffinoilmanufacturing

Packaging Sizes: 1L 3L 4L 5L 20L 25L 208L