PARAFFIN HYDRAULIC OIL
ISO-32/ SAE10W

The Right Choice in Lubricants

PARAFFIN HYDRAULIC OIL ISO-32/SAE10W is a high performance hydraulic oil formulated from high quality base oil and advanced additive packages to provide superior protection against equipment wear, corrosion, and oxidation. It is designed to meet stringent manufacturer requirements where hydraulic systems operate in severe and multi-ambient conditions.

FEATURES AND BENEFITS

- Superior anti-wear protection for extended equipment life
- Robust cleansing properties against sludge and other deposit build-up
- Superior protection against rust and corrosion

APPLICATION

- Hydraulic equipment subject to a wide variation in operating temperatures
- Hydraulic equipment subject to severe and high load operational conditions requiring anti-wear protection

TYPICAL TECHNICAL PROPERTIES

TEST PARAMETERS	TEST METHOD	TYPICAL VALUE
Viscosity Grade		10W, ISO-32
VISCOSITY @ 100 °C, cSt	ASTM D445	5.4
VISCOSITY @ 40 °C, cSt	ASTM D445	32
POUR POINT, °C	ASTM D97	-22
FLASH POINT, (C.O.C.)	ASTM D92	210
Density @15°C kg/l	ASTM D-1298	0.865
FOAM TES T, ml Seq. I	ASTM D892	10/0
Seq. II	ASTM D892	10/0
Seq. III	ASTM D892	0/0

Al Ghail Industrial Park - Ras Al Khaimah - United Arab Emirates
+971 7 266 7906 +971 50 327 2769
sales@paraffinlubricants.com www.paraffinlubricants.com
paraffinoilrefineryandmanufacturing paraffinoilmanufacturing

Packaging Sizes: 4L 5L 20L 25L 208L