



## PARAFFIN HYDRAULIC OIL VG-32

The Right Choice in Lubricants

**PARAFFIN HYDRAULIC OIL VG-32** is a high performance hydraulic oil formulated from high quality base oil and advanced additive packages to provide superior protection against equipment wear, corrosion, and oxidation. It is designed to meet stringent manufacturer requirements where hydraulic systems operate in severe and multi-ambient conditions.

### FEATURES AND BENEFITS

- Superior anti-wear protection for extended equipment life
- Robust cleansing properties against sludge and other deposit build-up
- Superior protection against rust and corrosion

### APPLICATION

- Hydraulic equipment subject to a wide variation in operating temperatures
- Hydraulic equipment subject to severe and high load operational conditions requiring anti-wear protection

### TYPICAL TECHNICAL PROPERTIES

TEST PARAMETERS	TEST METHOD	TYPICAL VALUE
Color		Transparant white
Viscosity Grade		32
VISCOSITY @ 100 °C, cSt	ASTM D445	5.5
VISCOSITY @ 40 °C, cSt	ASTM D445	32
POUR POINT, °C	ASTM D97	-27
FLASH POINT, (C.O.C.)	ASTM D92	210
Density @15°C kg/l	ASTM D-1298	0.865
FOAM TES T, ml Seq. I	ASTM D892	10/0
Seq. II	ASTM D892	10/0
Seq. III	ASTM D892	0/0



📍 Al Ghail Industrial Park - Ras Al Khaimah - United Arab Emirates

☎ +971 7 266 7906 📞 +971 50 327 2769 📧 📱

✉ sales@paraffinlubricants.com 🌐 www.paraffinlubricants.com

📘 paraffinoilrefineryandmanufacturing 📷 paraffinoilmanufacturing

Packaging Sizes: 4L 5L 20L 25L 208L